

Benchtop SMPS

Reliable DC power with a small footprint

Our benchtop Switchmode Power Supply (SMPS) rectifier features an innovative, compact design to provide users with an operational and installation advantage.

Dynapower benchtop SMPS rectifiers provide the reliability and functionality you need, while maximizing your space and cost savings. It is a solid-state AC-to-DC power conversion system, with sealed electronics and electrical component compartments that can withstand harsh, caustic environments.

This system provides a precisely controlled, high-current DC output with <2% AC Vrms content. Its high switching frequency enables a smaller package, less ripple, and higher efficiency, and provides for a faster control loop. Integrated controls include a digital display, on/off switch, voltage and current mode indication lights, and control pushbuttons. The benchtop SMPS also comes with a variety of analog remote interface options, including 4-20mA, 0-10V, and 0-5V.

System Advantages

- High efficiency power in a small footprint
- Low ripple content
- Standard configurations in-stock and available for next day delivery



TECHNICAL SPECIFICATIONS

Electrical

Input Voltage:	110V _{AC} 3PH / 220V _{AC} 3PH
Frequency:	60Hz (standard) / 50Hz (optional)
Output Voltage:	6-24V _{DC} (see matrix below)
Output Amps:	10-300A _{DC} (see matrix below)
Ripple:	2% at Full Output
Power Factor:	0.93 throughout operating range
Efficiency:	90% at rated output
Regulation Range:	10-100% of rated output
Control Precision:	Voltage/current at +/- 1%
Duty Cycle:	Designed for continuous operation at rated load

Environmental

Cooling:	Forced Air
Enclosure:	Stainless Steel Enclosure with Sealed Electronics
Dimensions (H x W x D):	5.25" x 19" x 23.25"
Max Ambient:	40°C

Controls

Integral digital display with push buttons

Communications Interface

Analog 4-20mA (Standard)
 Analog 0-10V (Optional)
 Analog 0-5V (Optional)

Protection Features

Over-Current
 Over-Voltage
 Over-Temperature

STANDARD CONFIGURATION OPTIONS


220V_{AC} Input

	AMPS					
VOLTS	10	25	50	100	200	300
6	✓	✓	✓	✓	✓	✓
12	✓	✓	✓	✓	✓	✓
15			✓	✓	✓	
18				✓	✓	
30				✓		

110V_{AC} Input

	AMPS			
VOLTS	10	25	50	100
6	✓	✓	✓	✓
12	✓	✓	✓	✓

Control Options



Analog Remote: Perfect for processes that do not require specialized outputs, our analog controls are designed to be as reliable and straightforward as possible, ensuring you get the unit control you need while withstanding the harshest environments.



Datasheets provided by Sensata Technologies, Inc., its subsidiaries and/or affiliates ("Sensata") are solely intended to assist third parties ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, valuation, and judgment in designing Buyer's systems and products. Sensata datasheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular datasheet. Sensata may make corrections, enhancements, improvements, and other changes to its datasheets or components without notice.

Buyers are authorized to use Sensata datasheets with the Sensata component(s) identified in each particular datasheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATASHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATASHEETS OR USE OF THE DATASHEETS, EXPRESS, IMPLIED, OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATASHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com. SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY, AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA. Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA



REGIONAL HEAD OFFICES

United States of America

Sensata Technologies

Attleboro, MA

Phone: 508-236-3800

E-mail: support@sensata.com

Netherlands

Sensata Technologies Holland B.V.

Hengelo

Phone: +31 74 357 8000

E-mail: support@sensata.com

China

Sensata Technologies China Co., Ltd.

Shanghai

Phone: +8621 2306 1500

E-mail: support@sensata.com

Copyright © 2023

Sensata Technologies, Inc.



85 Meadowland Drive, South Burlington, Vermont USA 05403

1.802.860.7200 | sales@dynapower.com

dynapower.com

