

CPS-3000 Energy Storage Inverter

The world's most advanced utility-scale energy storage inverter

Featuring a highly-efficient three-level topology, the CPS-3000 inverter is designed for four-quadrant energy storage applications and provides the perfect balance of performance, reliability, and cost effectiveness.

The CPS-3000 is a 3,000kVA, outdoor-rated unit that can be paralleled to meet the needs of any grid-tied or microgrid application enclosed in a NEMA 3R container that can be easily moved and allows for placement on gravel or concrete pylons for cost-effective installation.

The CPS-3000 inverter contains all required protective features, including an AC output breaker and DC disconnect switch. This creates a cost savings compared to other inverters that require additional add-on items needed for battery integration. In addition, our patented Dynamic Transfer™ feature monitors grid stability and will disconnect and transition to stand-alone mode if a disturbance is detected.



Key Technologies

- Islanded Operation (UF Mode)
- Dynamic Transfer
- Black Start
- Frequency Compensation Mode (F-Comp)
- Volt-VAR Compensation Mode (E-Comp)
- AC Current Limiting (In-Rush Current Handling in UF Mode)

TECHNICAL SPECIFICATIONS

Electrical

AC Input Voltage:	350V _{AC} / 480V _{AC} / 600V _{AC}
Grid Frequency:	60 Hz
Maximum Apparent Power:	1750kVA (@350V _{AC}) 2400kVA (@480V _{AC}) 3000kVA (@600V _{AC})
Maximum Real Power:	1750kW (@350V _{AC}) 2400kW (@480V _{AC}) 3000kW (@600V _{AC})
Maximum AC Current:	1444 A _{RMS} x 2
DC Voltage Range:	550-1500V _{DC} (@350V _{AC}) 740-1500V _{DC} (@480V _{AC}) 900-1500V _{DC} (@600V _{AC})
Maximum DC Current:	1720A _{DC} x 2
Power Factor:	0 – 1.00 Leading or Lagging
Current Harmonics:	IEEE 1547 Compliant, <5% TDD
Maximum Efficiency:	98.5%
CEC Efficiency:	97%

Environmental

Operating Temp:	-35 to +60°C, De-rated above +45°C
Max Elevation:	1000 Meters Full Power Up to 3000 Meters with Derating
Cooling:	Forced Air Cooled
Enclosure:	NEMA 3R/IP 54
Dimensions (HxWxD):	102" x 96" x 118"
Weight:	11,000 lbs

Certifications & Standards Compliance

UL 1741 SA	CSA 22.2 #107.1
IEEE 1547	IEEE 519

Hardware Protections

AC Breaker with Shunt Trip	DC Input Fuses
AC Surge Protection	DC Pre-charge
DC Disconnect	

Software Protections

Battery Voltage and Current Curtail Limits to protect battery
AC Current Limiting Pending
DC Over/Under Voltage, Over Current faults
AC Over/Under Voltage, Over/Under Frequency, Over Current faults
Anti-islanding Protection (Open Phase at inverter terminals)
Temperature Monitoring and protective power curtailment



CPS-3000 Outdoor

Datasheets provided by Sensata Technologies, Inc., its subsidiaries and/or affiliates ("Sensata") are solely intended to assist third parties ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, valuation, and judgment in designing Buyer's systems and products. Sensata datasheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular datasheet. Sensata may make corrections, enhancements, improvements, and other changes to its datasheets or components without notice.

Buyers are authorized to use Sensata datasheets with the Sensata component(s) identified in each particular datasheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATASHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATASHEETS OR USE OF THE DATASHEETS, EXPRESS, IMPLIED, OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATASHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com. SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY, AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA. Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA



REGIONAL HEAD OFFICES

United States of America

Sensata Technologies
Attleboro, MA
Phone: 508-236-3800
E-mail: support@sensata.com

Netherlands

Sensata Technologies Holland B.V.
Hengelo
Phone: +31 74 357 8000
E-mail: support@sensata.com

China

Sensata Technologies China Co., Ltd.
Shanghai
Phone: +8621 2306 1500
E-mail: support@sensata.com

Copyright © 2023
Sensata Technologies, Inc.



85 Meadowland Drive, South Burlington, Vermont USA 05403

1.802.860.7200 | sales@dynapower.com

dynapower.com

