

CPS-1250 & CPS-2500 Fuel Cell Inverters

UL-1741 Ed. 3 certified technology supporting fuel cell to grid power conversion

The CPS-1250 and CPS-2500 utility interactive inverters are ideal for connecting stationary hydrogen fuel cells to an AC grid. CPS Fuel Cell Inverters are capable of operating in grid-tied and standalone mode and feature advanced control algorithms to support both modes of operation.

Available in outdoor configurations from 585kVA to 2672kVA, modular units can be paralleled to scale with project size to meet fuel cell array requirements. Designed for utility interconnection, CPS Fuel Cell Inverters contain all required protective features and comply with applicable IEEE, IEC, CE, and UL standards.

The CPS-1250 and CPS-2500 offer best-in-class control modes including Dynamic Transfer, isochronous and droop-based islanding, black start capability with robust inrush AC current limiting, and are capable of power control and DC voltage control with active current and voltage curtailment to ensure fuel cell operation is maintained within optimal operating points.



System Advantages

- Proven 5th generation technology
- Designed for utility interconnection
- Capable of operating over a wide DC voltage range (511–1500V_{DC})
- Seamless transfer from grid-tied to stand-alone mode with patented Dynamic Transfer feature



Advanced Control Modes

- Islanded Operation (UF Mode)
- Dynamic Transfer
- Black Start (In-Rush Current Handling in UF Mode)
- Frequency Compensation Mode (F-Comp)
- VAR Compensation Mode (E-Comp)
- AC Current Limiting
- Low Voltage Ride-Through (LVRT) with Active Current Injection
- Multiple Parallel Inverter Microgrid Mode

CPS-2500 TECHNICAL SPECIFICATIONS

Electrical

DC Voltage Range:	511–1500V _{DC} (@350–800V _{AC})
Maximum DC Current:	2340A _{DC}
Power Factor:	Four quadrant
Current Harmonics:	IEEE 1547 Compliant, <5% TDD
AC Input Voltage:	800V _{AC} / 690V _{AC} / 660V _{AC} / 630V _{AC} / 600V _{AC} 540V _{AC} / 480V _{AC} / 415V _{AC} / 350V _{AC}
Grid Frequency:	60Hz (50Hz available in 2024)
Maximum Apparent Power:	2672 kVA (@800V _{AC}) 2304 kVA (@690V _{AC}) 2204 kVA (@660V _{AC}) 2104 kVA (@630V _{AC}) 2004 kVA (@600V _{AC}) 1803 kVA (@540V _{AC}) 1603 kVA (@480V _{AC}) 1386 kVA (@415V _{AC}) 1169 kVA (@350V _{AC})
Maximum Real Power:	2672 kW (@800V _{AC}) 2304 kW (@690V _{AC}) 2204 kW (@660V _{AC}) 2104 kW (@630V _{AC}) 2004 kW (@600V _{AC}) 1803 kW (@540V _{AC}) 1603 kW (@480V _{AC}) 1386 kW (@415V _{AC}) 1169 kW (@350V _{AC})
Maximum AC Current:	1928A _{RMS}
Maximum Projected Efficiency:	98.58 @1500V _{DC}

Environmental

Operating Temp:	-30 to +60°C, De-rated above +45°C
Max Elevation:	1,000 Meters Full Power Up to 3,000 Meters with De-rating
Cooling:	Forced Air Cooled
Enclosure:	NEMA 3R/IP 54
Dimensions (HxWxD):	80" x 85" x 43"
Weight:	3,970 lbs

Certifications & Standards Compliance*

UL1741 Ed. 3
UL 1012 and IEC 62477 for unidirectional operation
CE
IEEE 1547
CSA 22.2 #107.1
IEEE 519

Hardware Protections

AC Breaker with Shunt Trip
AC Surge Protection
DC Input Fuses
DC Pre-Charge

Software Protections

Current and Voltage Curtailment Limits
AC Current Limiting Pending
DC Over/Under Voltage, Over Current Fault
AC Over/Under Voltage, Over/Under Frequency, Over Current Faults
Anti-Islanding Protection (Open Phase at Inverter Terminals)
Temperature Monitoring and Protective Power Curtailment

*Pending



CPS-1250 TECHNICAL SPECIFICATIONS

Electrical

DC Voltage Range:	511–1500V _{DC} (@350–800V _{AC})
Maximum DC Current:	1170A _{DC}
Power Factor:	Four quadrant
Current Harmonics:	IEEE 1547 Compliant, <5% TDD
AC Input Voltage:	800V _{AC} / 690V _{AC} / 660V _{AC} / 630V _{AC} / 600V _{AC} 540V _{AC} / 480V _{AC} / 415V _{AC} / 350V _{AC}
Grid Frequency:	60Hz (50Hz available in 2024)
Maximum Apparent Power:	1336 kVA (@800V _{AC}) 1152 kVA (@690V _{AC}) 1102 kVA (@660V _{AC}) 1052 kVA (@630V _{AC}) 1002 kVA (@600V _{AC}) 902 kVA (@540V _{AC}) 802 kVA (@480V _{AC}) 693 kVA (@415V _{AC}) 585 kVA (@350V _{AC})
Maximum Real Power:	1336 kW (@800V _{AC}) 1152 kW (@690V _{AC}) 1102 kW (@660V _{AC}) 1052 kW (@630V _{AC}) 1002 kW (@600V _{AC}) 902 kW (@540V _{AC}) 802 kW (@480V _{AC}) 693 kW (@415V _{AC}) 585 kW (@350V _{AC})
Maximum AC Current:	964A _{RMS}
Maximum Projected Efficiency:	98.58 @1500V _{DC}

Environmental

Operating Temp:	-30 to +60°C, De-rated above +45°C
Max Elevation:	1,000 Meters Full Power Up to 3,000 Meters with De-rating
Cooling:	Forced Air Cooled
Enclosure:	NEMA 3R/IP 54
Dimensions (HxWxD):	80" x 49" x 43"
Weight:	1,980 lbs

Certifications & Standards Compliance*

UL1741 Ed. 3
UL 1012 and IEC 62477 for unidirectional operation
CE
IEEE 1547
CSA 22.2 #107.1
IEEE 519

Hardware Protections

AC Breaker with Shunt Trip
AC Surge Protection
DC Input Fuses
DC Pre-Charge

Software Protections

Current and Voltage Curtailment Limits
AC Current Limiting Pending
DC Over/Under Voltage, Over Current Faults
AC Over/Under Voltage, Over/Under Frequency, Over Current Faults
Anti-Islanding Protection (Open Phase at Inverter Terminals)
Temperature Monitoring and Protective Power Curtailment

*Pending

DYNAPower
Part of Sensata Technologies

85 Meadowland Drive, South Burlington, Vermont USA 05403

1.802.860.7200 | sales@dynapower.com

dynapower.com



Datasheets provided by Sensata Technologies, Inc., its subsidiaries and/or affiliates ("Sensata") are solely intended to assist third parties ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, valuation, and judgment in designing Buyer's systems and products. Sensata datasheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular datasheet. Sensata may make corrections, enhancements, improvements, and other changes to its datasheets or components without notice.

Buyers are authorized to use Sensata datasheets with the Sensata component(s) identified in each particular datasheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATASHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATASHEETS OR USE OF THE DATASHEETS, EXPRESS, IMPLIED, OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATASHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com. SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY, AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA. Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA



REGIONAL HEAD OFFICES

United States of America

Sensata Technologies
Attleboro, MA
Phone: 508-236-3800
E-mail: support@sensata.com

Netherlands

Sensata Technologies Holland B.V.
Hengelo
Phone: +31 74 357 8000
E-mail: support@sensata.com

China

Sensata Technologies China Co., Ltd.
Shanghai
Phone: +8621 2306 1500
E-mail: support@sensata.com

Copyright © 2023
Sensata Technologies, Inc.



85 Meadowland Drive, South Burlington, Vermont USA 05403

1.802.860.7200 | sales@dynapower.com

dynapower.com

