

DPS-1000 Converter

The most flexible DC Converter on the market

POWER CONVERSION FOR SOLAR PLUS STORAGE, HYDROGEN, AND EV APPLICATIONS

This bi-directional 1000kW DC-DC converter is designed to interface battery energy storage with new and existing 1000V and 1500V central inverter-based applications.

The DPS-1000 is ideal for utility-scale solar plus storage installations, with maximum flexibility to also meet power conversion needs for hydrogen and EV applications. It offers advanced features including automated clipping recapture and low voltage harvesting that increase project revenues, while its DC-coupled architecture reduces installation and regulatory costs.

This DC-DC converter can operate in voltage, current, and power control modes, and is capable of on-the-fly switching between modes. Designed to be easily scaled, up to 6 units can be paralleled for up to 6MW of power harvesting.



System Advantages:

- Reduce installation and regulatory costs through DC-coupled architecture
- Scalable power up to 6MW with paralleled units

Key Technologies

- Clipping Recapture
- Maximum Power Point Tracking
- Curtailment Recapture
- Energy Time Shifting
- Ramp Rate Control

TECHNICAL SPECIFICATIONS

Electrical

DC Input Voltage Range (Battery Port):	100–1500V _{DC}
DC Input Voltage Range (PV Port):	100–1500V _{DC}
Maximum Power Rating:	833kW (@1000V _{DC}) 1000kW (@1200-1500V _{DC})
Maximum Current Rating:	+/-833A _{DC}
Maximum Efficiency:	99%
Efficiency:	98.5%
Aux/Controls Power:	Customer supplied 120V, 1-ph, 60Hz, 1.2kVA service Customer supplied 230V / 277V, 1-ph, 50Hz, 1.2kVA service

Environmental

Operating Temp:	-35 to +60°C
Cooling:	Forced Air Cooled
Enclosure:	UL 3R/IP 54
Max Elevation:	1000 Meters Full Power, 3000 Meters with Derating
Dimensions (L x W x H):	31.4" x 37.8" x 85.9"
Weight:	1540 lbs
Cable Connections:	Side or bottom entry

Certifications & Standards Compliance*

UL 1741
CSA C22.2 #107.1
UL / IEC 62109-1/2
IEC / EN 61000-6-4
IEC / EN 61000-6-2
CISPR 11 2015-6 / EN 55011
FCC Part 15 Class A

Hardware Protections

DC Contactor and Precharge on Battery Port

* Pending

Software Protections

DC Over-voltage / Under-voltage	Over-temperature
DC Over-current	Fuse monitoring

Options

Integrated DC Fuses	DC Power Circuit SPD
DC High Accuracy Metering	Insulation Monitoring

User Interface

Remote Communications:	Modbus TCP/IP
Local Indicators:	Lamps on front panel indicating operation mode & alarm/fault status



DYNAPOWER

85 Meadowland Drive, South Burlington, Vermont USA 05403

1.802.860.7200 | sales@dynapower.com

[dynapower.com](https://www.dynapower.com)

