

MV Integrated PowerSkid™

Integrated, easy-to-install skid for medium voltage applications



The MV Integrated PowerSkid™ combines our highly efficient three-level bi-directional PCS with medium-voltage components to create an ideal solution for quick integration.

The MV Integrated PowerSkid is delivered on a pre-configured integrated skid for simplified installation and commissioning. Designed with integrated medium-voltage components, the PowerSkid offers maximum performance in a convenient package.

Our next-generation CPS-2500 PCS offers industry-leading power density and efficiency that will scale to meet the needs of large-scale energy storage applications.

System Advantages

- Quick and easy installation with factory assembled products
- Plug-and-play concept for easy integration
- Simplified procurement
- Simplified commissioning



CPS-2500 TECHNICAL SPECIFICATIONS

Electrical

AC Input Voltage:	480-800V _{AC}
Grid Frequency:	60 Hz
Maximum Apparent Power:	5337 kVA (800V _{AC}) 4600 kVA (690V _{AC}) 4000 kVA (600V _{AC}) 3600 kVA (480V _{AC})
Maximum Real Power:	5337 kVA (800V _{AC}) 4600 kVA (690V _{AC}) 4000 kVA (600V _{AC}) 3600 kVA (480V _{AC})
Maximum AC Current:	1928 A _{RMS} (3856A _{RMS})
DC Voltage Range:	771-1500VDC (@480-800V _{AC})
Maximum DC Current:	2340A _{DC} (4680A _{DC})
Power Factor:	Four Quadrant
Current Harmonics:	IEEE 1547 Compliant, <5% TDD
Maximum Efficiency:	98.58 @1500V _{DC} & 98.70 @1280V _{DC}

Environmental

Operating Temp:	-35 to +60°C, De-rated above +40°C
Max Elevation:	1000 Meters Full Power Up to 3000 Meters with Derating
Cooling:	Forced Air Cooled
Enclosure:	NEMA 3R/IP 54
Skid Dimensions (L X W X H):	240" x 96" x 108"

Certifications & Standards Compliance

UL1741 Ed. 3
IEEE 1547
CSA 22.2 #107.1
IEEE 519

TRANSFORMER TECHNICAL SPECIFICATIONS

Overview

Construction Type:	Hermetically Sealed with Corrugated Walls
Distribution:	3-Phase
Power:	4-5.3MVA
Cooling Class:	ONAN (KNAN and FR3 also available)
HV Winding:	11-34.5 kV Delta
Alternative MV AC Standard Options:	34.5kV, 12.45kV
LV Winding:	480-800V _{AC}



Datasheets provided by Sensata Technologies, Inc., its subsidiaries and/or affiliates ("Sensata") are solely intended to assist third parties ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, valuation, and judgment in designing Buyer's systems and products. Sensata datasheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular datasheet. Sensata may make corrections, enhancements, improvements, and other changes to its datasheets or components without notice.

Buyers are authorized to use Sensata datasheets with the Sensata component(s) identified in each particular datasheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATASHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATASHEETS OR USE OF THE DATASHEETS, EXPRESS, IMPLIED, OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATASHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com. SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY, AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA. Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA



REGIONAL HEAD OFFICES

United States of America

Sensata Technologies
Attleboro, MA
Phone: 508-236-3800
E-mail: support@sensata.com

Netherlands

Sensata Technologies Holland B.V.
Hengelo
Phone: +31 74 357 8000
E-mail: support@sensata.com

China

Sensata Technologies China Co., Ltd.
Shanghai
Phone: +8621 2306 1500
E-mail: support@sensata.com

Copyright © 2023
Sensata Technologies, Inc.



85 Meadowland Drive, South Burlington, Vermont USA 05403

1.802.860.7200 | sales@dynapower.com

dynapower.com

